Sentry Smart CDU

Key Features

- > High Density: Single-power input feed; 27 outlets; Quantity (21) NEMA 5-20R and (6) NEMA L6-20R outlets per CDU.
- > High Power Distribution: 208V
 Wye three-phase power;
 20-Amp power input feed.
- > Multiple Voltage Outputs: 120V & 208V output
- > Input Current Monitor: Precisely measure the aggregate current draw (in amps) on each phase. On-site verification of the input current with the LED digital display. Remote verification via web browser or serial screen.
- > IP Access & Security: Web interface, SSL, SSH, Telnet, SNMP, FTP, SNTP, Syslog, LDAP, LDAPS, RADIUS, TACACS and RS-232 access
- > Alerts: Provide automated SNMP-based alarms or email alerts for power and environmental conditions
- > Environmental Monitoring: Each Smart CDU supports two external temperature & humidity probes and reports conditions thru the user interface without the need for additional IP addresses
- > Add an Expansion Module: Connect the Smart Expansion CDU (CL) to a Master unit (CS) for power monitoring of separate power circuits from a single IP address

CS-27VY-004 with NEMA 5-20R and L6-20R Outlets

High Density Power Distribution

The Smart Cabinet Distribution Units (CDU) provide reliable power distribution combined with local and remote power monitoring and environmental monitoring via IP. Use the network interface to view power, temperature and humidity levels via Web browser, or receive SNMP–based alarms and email alerts when conditions exceed defined thresholds.

The Smart CDU family has the capability to daisy chain units together. The Expansion CDU Module gives the ability to use one IP address across different power circuits.

Additional Benefits:



Input Current Monitoring

The NEW Digital True RMS monitoring, with improved accuracy, is critical to preventing overloads in high-density computing environments. LED digital displays on the CDU enclosure report the input current of each phase for simple load balancing.



Temperature and Humidity

The Smart CDU supports two external 10' (3m) probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alerts or email notifications when conditions exceed defined thresholds.



Linking for Smart CDU (Expansion Modules)

The Smart CDU family has the capability to daisy chain units together. The Expansion Module provides the ability to link two power circuits under one IP address.

Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
CS-27VYL123-004	208V, 3-phase Wye,	20A	NEMA L21-20P	(21) NEMA 5-20R	69.0 x 1.75 x 3.5 in.
CL-27VYL123-004*	50/60Hz		Cordset, 10 ft (3m)	(6) NEMA L6-20R	(1753 x 44 x 89 mm)

* CL part numbers refer to the Expansion CDU

Additional Features and Specifications

Agency Approvals

- > US & Canada (cTUVus mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > FCC Class A, Part 15
- >CE
- > EMC CISPR 22 Class A

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS
- > SSLv3/TLSv1
- > SNMPv2
- > SSHv2
- > Telnet
- > LDAPS/LDAPv3
- > RADIUS
- >TACACS+
- > RS-232 (Serial)

Accessories

> Optional Temperature & Humidity Probe

- EMTH-1-1 Temperature & Humidity Probe, 10 ft (3m)

- > SPM (Sentry Power Manager) Appliance:
 - Monitor and Manage multiple Sentry CDU's
 - Monitor and Manage all alarm conditions
 - Reporting and Trending
 - Group or Cluster outlets for reboot and power information
- > Environmental Monitor

- EMCU-1-1B allows up to (2) additional temperature & humidity probes, (1) water sensor, (4) dry contact closures, (1) analog-to-digital contact sensor. Includes (1) temperature/humidity probe with unit.





Server Technology

HEADQUARTERS - NORTH AMERICA Server Technology, Inc. 1040 Sandhill Drive Reno, NV 89521 United States 1.775.284.2000 Tel 1.775.284.2065 Fax sales@servertech.com www.servertech.com EMEA Server Technology Intl Sienna Court The Broadway Maidenhead Berkshire SL6 1NJ United Kingdom +44 (0) 1628 509053 Tel +44 (0) 1628 509100 Fax salesint@servertech.com APAC Server Technology Intl 37th Floor, Singapore Land Tower 50 Raffles Place Singapore 048623 +65 (0) 6829 7008 Tel +65 (0) 6234 4574 Fax salesint@servertech.com

© Server Technology, Inc. 1/2011 version. Information in this document is subject to change without notice. Sentry and Server Technology are trademarks of Server Technology, Inc. Patents Pending. Printed in US.